

Cleaning and Care Instructions

The surface of Acrygloss is covered with a PE protective film up to the time of use. Normally the PE protective film stays on the surface during processing and installation, up to the point of everyday use in the kitchen or bathroom. After removal of the film, the surface is ready for daily use.

We recommend using VuPlex, the most simple and effective product to remove static and clean the Acrygloss surface safely, leaving the surface with a high gloss.

IMPORTANT: the use of abrasive cleaning and scouring agents can cause damage and should be avoided. The surface of Acrygloss is, however, resistant to many chemicals. In case of doubt, suitability and resistance should be checked on a sample surface. Only use mild, non-abrasive cleaners.

The HIPS backing material is not as chemically resistant as the Acrygloss facing material. HIPS should be cleaned with warm soapy water.

Care should be taken to ensure hot pans and implements do not come into contact with Acrygloss.

Warranty

The Consumer Guarantees Act applies to Acrygloss doors by Sage Doors Ltd. All Acrygloss doors and panels come with a 10 year guarantee to the original purchaser against all defects in the materials.

Please Note: the guarantee will not apply where the product has been damaged after manufacture through misuse, negligent cleaning, water damage, or maintenance.

The Acrygloss panel surface is waterproof. However, while the Laseredge is 97% water proof, care should be taken to ensure unclashed edges are not exposed to water or steam.

Liability will be limited to replacement of the doors and panels. Sage Doors Ltd will not meet any costs of refitting or installation. Under no circumstances will liability exceed the current purchase price of the original goods.